

外徑 D	厚度 T	長度 L	種別	主筋 PC		CNS 規格彎矩 (KN · m)		長期容許軸向荷重 Pa	參考重量 W
				直徑 (mm)	支數 (pcs)	開裂 (Mcr)	破壞 (Mu)		
250	50	6-8	A	7.1	6	15	22.5	350	82
300	60	6-8	A	9.0	4	25	37.5	500	118
		6-10	B	9.0	6	30	48.0	450	
		6-13	C	9.0	8	35	63.0	450	
350	65	6-10	A	9.0	6	35	52.5	600	151
		6-14	B	9.0	8	42	67.2	550	
		6-14	C	9.0	10	50	90.0	550	
400	75	6-10	A	9.0	6	55	82.5	800	199
		6-16	B	9.0	10	65	104.0	750	
		6-16	C	9.0	12	75	135.0	750	
		6-16	D	10.7	12	90	180.0	700	
450	80	6-10	A	9.0	8	75	112.5	1000	242
		6-14	B	9.0	10	92	147.2	950	
		6-14	C	9.0	16	110	198.0	900	
		6-14	D	10.7	14	125	250.0	850	
500	90	6-10	A	9.0	10	105	157.5	1250	301
		6-16	B	9.0	12	125	200.0	1200	
		6-16	C	9.0	18	150	270.0	1150	
		6-16	D	10.7	18	170	340.0	1050	
600	100	6-10	A	9.0	12	170	255.0	1700	408
		6-16	B	9.0	18	215	344.0	1600	
		6-16	C	9.0	24	250	450.0	1550	
		6-16	D	10.7	24	290	580.0	1450	
700	110	6-10	A	9.0	16	270	405.0	2200	530
		6-16	B	9.0	22	330	528.0	2100	
		6-16	C	9.0	30	380	684.0	2000	
		6-16	D	10.7	30	450	900.0	1900	
800	120	6-10	A	9.0	20	400	600.0	2800	666
		6-16	B	9.0	30	500	800.0	2600	
		6-16	C	9.0	38	550	990.0	2500	
		6-16	D	10.7	38	650	1300	2350	

900	130	6-16	B	10.7	24	650	1040	3250	817
		6-16	C	11.2	30	750	1350	3100	
		6-16	D	11.2	38	850	1700	2900	
1000	140	6-16	B	10.7	30	900	1440	3900	983
		6-16	C	11.2	34	1050	1890	3700	
		6-16	D	11.2	36	1200	2400	3500	
		6-10	C	12.6	40	1700	3060	5150	

業 務 連 絡 電 話
0975-326558 陳 韋 安